

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau




(43) International Publication Date
22 July 2004 (22.07.2004)

PCT

(10) International Publication Number
WO 2004/061508 A1

- (51) International Patent Classification⁷: **G02B 6/44**
- (21) International Application Number:
PCT/KR2003/001541
- (22) International Filing Date: 31 July 2003 (31.07.2003)
- (25) Filing Language: Korean
- (26) Publication Language: English
- (30) Priority Data:
10-2003-0000888 7 January 2003 (07.01.2003) KR
- (71) Applicant (for all designated States except US): **LG CABLE LTD.** [KR/KR]; 19-20F Asem Tower 159 Samsung-dong, Gangnam-gu, Seoul 135-090 (KR).
- (72) Inventors; and
- (75) Inventors/Applicants (for US only): **PARK, Chan-Yong** [KR/KR]; 305-603 Deungchon APT., Deungchon-dong, Gangseo-gu, Seoul 157-030 (KR). **LEE, Bong-Hoon** [KR/KR]; 732-1301 Best Town, Cheoncheon-dong, Janggan-gu, Suwon-si, Gyeonggi-do 440-330 (KR).
- (54) Title: **OPTICAL FIBER UNIT FOR AIR BLOWN INSTALLATION AND MANUFACTURING METHOD THEREOF**
- (74) Agents: **LEE, Sang-Yong** et al.; 4F., Byukcheon Bldg., 1597-5, Seocho-dong, Seocho-gu, Seoul 137-876 (KR).
- (81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).
- Published:
— with international search report
- For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.



(57) Abstract: An optical fiber unit for air blown installation includes at least one optical fiber having a core layer and a clad layer; a protective layer coated on the surface of the optical fiber; and protrusions made of polymer resin and formed on the outer circumference of the protective layer in a banded shape. The protrusions may be formed either by supplying polymer resin to the outer circumference of the optical fiber with passing the optical fiber through an extrusion dice in which grooves of a predetermined shape are formed on a hollow inner circumference thereof, or by supplying polymer resin to the outer circumference of the optical fiber through nozzles with moving the optical fiber in a longitudinal direction.